


# Fielder's Choice 10000 52



**SPORTTURF™**




## PROPERTY


## DESCRIPTION

**FL416S-52**

<b>Primary Yarn Polymer</b>	Polyethylene; Polypropylene
<b>Yarn Cross Section</b>	Polyethylene Slit Film; Texturized Polypropylene
<b>Standard Color</b>	Field; Terra Cotta
<b>Additional Colors Available*</b>	White
<b>UV Stabilized</b>	Yes
<b>Fabric Construction</b>	Tufted
<b>Primary Backing</b>	Dual layered woven polypropylene
<b>Coating Type</b>	SilverBack™ Polyurethane
<b>Perforations</b>	Yes
<b>Polyethylene Yarn Denier/Ends</b>	10000/1 (Slit) 4600/8 (Texturized PP)
<b>Infill</b>	Preferred Infill
<b>Pile Height</b>	1 7/8"
<b>Pile Weight</b>	52 oz.




### CURB



### EQUIPMENT

Standard Line and Field Colors\*



## APPLICATION

This is a field product. This product should be installed outdoors on a compacted aggregate base. Custom designed for baseball, Fielder's Choice has the added durability designed to reduce infill splash and migration which is extremely important in gameplay.



\*Custom colors available upon request

## TESTING

## FIELDER'S CHOICE 10000 52

### FINISHED FABRIC

### ENGLISH SYSTEM

### METRIC SYSTEM

### ASTM TEST

#### Nominal Specification

	<i>Value</i>	<i>Units</i>	<i>Value</i>	<i>Units</i>	<i>Method</i>
<b>Pile Height (Nominal)</b>	1 7/8	In.	47.63	mm.	D-5823
<b>Face Weight</b>	52	oz/yd <sup>2</sup>	1763	g/m <sup>2</sup>	D-5848
<b>Total Fabric Weight</b>	79	oz/yd <sup>2</sup>	2678	g/m <sup>2</sup>	D-5848
<b>Primary backing Weight</b>	7.4	oz/yd <sup>2</sup>	251	g/m <sup>2</sup>	D-5848
<b>Secondary Coating Weight</b>	22	oz/yd <sup>2</sup>	746	g/m <sup>2</sup>	D-5848
<b>Tuft Bind</b>	>10	lbs.	>4.5	Kg.	D-1335
<b>Grab Tear Strength (Average)</b>	>200	lbs.	>91	Kg.	D-2256
<b>Lead Content</b>	<50	ppm	<50	ppm	D-2765
<b>Total Yarn Linear Density</b>	14,600	Denier	16,220	D-Tex	D-1577
<b>Tensile Strength (Slit PE)</b>	8	lbs.	3.63	Kg.	D-5034
<b>Tensile Strength (Texturized PP)</b>	3.7	lbs.	1.7	Kg.	D-789
<b>Stitch Rate</b>	9.75	Per 3"	12.77	Per 10 cm	D-5793
<b>Machine Gauge</b>	1/2	In.	1.27	Cm.	D-5793
<b>Flammability</b>	TEST	PASSED	TEST	PASSED	D-2859
<b>Water Permeability w/infill</b>	>30	In./Hr.	>72	Cm./Hr.	F-1551
<b>Fiber Thickness (Slit PE)</b>	9.4	mils	100	microns	D-3218
<b>Fabric Width</b>	15	Ft.	4.6	M	None

8/25/2023