
GameChanger 40Z





Polyethylene

FL420Z-40

Primary Yarn Polymer

Yarn Cross Section

Polyethylene Monofilament; Polyethylene Slit Film

Standard Color

PROPERTY

Field; Field/Lime

DESCRIPTION

Additional Colors Available*

White, Yellow, Red, Florida Blue, Black, Orange, Terra Cotta

UV Stabilized

Tufted

Fabric Construction

Primary Backing

Dual layered woven polypropylene

Coating Type

SilverBack™ Polyurethane

Perforations

Yes

Polyethylene Yarn Denier/Ends

1800x4 (Mono) 5000/1 (Slit)

Recommended Infill

1 lb. Silica Sand; 3.25 lbs. SBR Rubber

Pile Height


2"

Pile Weight 40 oz.

SLOPE SUBGRADE @ .5% FOWARDS COLLECTOR TRENCH GEOTEXTILE FABRIC, COVER ENTIRE SUBGRADE PANEL DRAIN RESILIENT SURFACING INFILLED SYNTHETIC
TURF SYSTEM 6" X 12" CONC. CURB W/ 9" PERFORATED COLLECTOR SUB-DRAIN

INSTALL FILTER FABRIC BELOW AGGREGATE BASE COURSE AND AT BOTTOM & SIDES OF TRENCH

CURB



APPLICATION

Standard Line and Field Colors*















This is a multi sport field product. This product should be installed outdoors on a compacted aggregate base. The 3C "Triple Coverage" system allows for more face yarn to show off its beautiful colors. This 12,200 denier system will keep your field looking newer, longer with over 50% more yarn denier above the rubber infill.

















TESTING

GAMECHANGER 40Z

FINISHED FABRIC	ENGLISH SYSTEM		METRIC SYSTEM		ASTM TEST
Nominal Specification	Value	Units	Value	Units	Method
Pile Height (Nominal)	2	In.	50.8	mm.	D-5823
Face Weight	40	oz/yd²	1356	g/m²	D-5848
Total Fabric Weight	67	oz/yd²	2271	g/m²	D-5848
Primary backing Weight	7.4	oz/yd²	251	g/m²	D-5848
Secondary Coating Weight	22	oz/yd²	746	g/m²	D-5848
Tuft Bind	>10	lbs.	>3.6	Kg.	D-1335
Grab Tear Strength (Average)	>200	lbs.	>91	Kg.	D-2256
Lead Content	<50	ppm	<50	ppm	D-2765
Total Yarn Linear Density	12,200	Denier	13,554	D-Tex	D-1577
Tensile Strength (Mono)	16	lbs.	7.26	Kg.	D-5034
Tensile Strength (Slit)	8	lbs.	3.6	Kg.	D-789
Stitch Rate	8	Per 3"	10.49	Per 10 cm	D-5793
Machine Gauge	1/2	In.	1.27	Cm.	D-5793
Flammability	TEST	PASSED	TEST	PASSED	D-2859
Water Permeability w/infill	>30	In./Hr.	>76	Cm./Hr.	F-1551
Fiber Thickness (Mono)	22.0	mils	310	microns	D-3218
Fiber Thickness (Slit)	9.4	mils	100	microns	D-3218
Fabric Width	15	Ft.	4.6	М	None

