


PROPERTY


DESCRIPTION

PL929

| | |
|--|--|
| Primary/Stalk Yarn Polymer | Polyethylene |
| Secondary/Thatch Yarn Polymer | Polypropylene |
| Yarn Cross Section | Polyethylene Monofilament Classic Spine/ Texturized Polypropylene |
| Standard Color | Field with Forest/Olive Thatch |
| Additional Colors* | Red; White; Blue; Yellow; Black |
| UV Stabilized | Yes |
| Fabric Construction | Tufted |
| Primary Backing | Dual Layered Woven Polypropylene |
| Coating Type | SilverBack™ Polyurethane |
| Perforations | Yes |
| PE Monofilament Yarn Denier/Ends | 10800/6 |
| Texturized Polypropylene Denier/Ends (Thatch) | 4600/8 |
| Pile Height | 1 ¼" |
| Pile Weight | 60 oz. |



CURB



EQUIPMENT

APPLICATION

This is a signature Playground product with a thatch system which provides added body, reducing the amount of infill needed. The four color blend of this surface provides a truly authentic look and feel that resembles a natural lawn. This product can also be used for landscapes, pet areas, fringes, and much more. This product can be installed indoors or outdoors on concrete or a compacted aggregate base.



*Custom colors available upon request



TESTING

PL929

FINISHED FABRIC

ENGLISH SYSTEM

METRIC SYSTEM

ASTM TEST

| <i>Nominal Specification</i> | <i>Value</i> | <i>Units</i> | <i>Value</i> | <i>Units</i> | <i>Method</i> |
|-------------------------------------|--------------|--------------------|--------------|------------------|---------------|
| Pile Height (Nominal) | 1.25 | In. | 31.75 | mm. | D-5823 |
| Face Weight | 60 | oz/yd ² | 2,034 | g/m ² | D-5848 |
| Total Fabric Weight | 87 | oz/yd ² | 2,949 | g/m ² | D-5848 |
| Primary Backing Weight | 7.4 | oz/yd ² | 251 | g/m ² | D-5848 |
| Secondary Coating Weight | 20 | oz/yd ² | 746 | g/m ² | D-5848 |
| Tuft Bind | >10 | lbs. | >3.6 | kg. | D-1335 |
| Grab Tear Strength (Average) | >200 | lbs. | >91 | kg. | D-2256 |
| Lead Content | <50 | ppm | <50 | ppm | D-2765 |
| Total Yarn Linear Density | 13,600 | Denier | 15,109 | D-Tex | D-1577 |
| Stitch Rate | 12.5 | Per 3" | 16.39 | Per 10 cm | D-5793 |
| Machine Gauge | 3/8 | In. | .9525 | cm | D-5793 |
| Flammability | TEST | PASSED | TEST | PASSED | D-2859 |
| Water Permeability w/Infill | N/A | In/hr | >76 | cm/hr | F-1551 |
| Fabric Width | 15 | Ft. | 4.6 | M | None |



8/28/2023